

IN THE SPECIFICATION

Please amend paragraphs 19 and 24 as follows.

[0019] For one embodiment, the channel 120 may include a keyboard interface 122 [(not shown)]. For another embodiment, the support arm 110 may include a keyboard cable 123 [(not shown)]. The keyboard interface 122 may be coupled with one end of the [the] keyboard cable 123 when the support arm 110 is coupled with the display section 105 at the channel 120. For one embodiment, another end of the keyboard cable 123 is coupled with a keyboard 150 located at the top of the base section 101, as illustrated in **Figure 3A**. The keyboard 150 may be used to input information into the computer system 100.

[0024] **Figure 5A** illustrates one example of the computer system 100 in a laptop mode, in accordance with one embodiment. In the laptop mode, the support arm 110 is attached to the base section 101, and the display section 105 may be placed in a generally upright position relative to the base section 101. For example, when the display screen 109 is positioned to generally face the keyboard 150, the display section 105 may rest against the support arm 110 by joining the lip 113 of the support arm 110 into the channel 120. This may also couple the keyboard cable 123 in the support arm 110 with the keyboard interface 122 in the channel 120. In this example, the display section 105 may form an angle 500 with the base section 101, and the computer system 100 may be considered to be in the laptop mode. For one embodiment, the keyboard 150 may be a wireless keyboard. In this situation, there may not be a keyboard interface in the channel 120, and there may not be a keyboard cable in the support arm 110.